

2550W LED Lunar Lighting Tower®

Total LED Efficacy of 586,500 Lumens from a SINGLE light head

“We Leave Our Competitors in the dark”



PATENTED TECHNOLOGY

ANTI-GLARE



www.LunarLighting.com

2550W LED Lunar Lighting Tower®

360° Anti-Glare Portable LED Light

Fully directional lighting: 5x independent light segments of 72° per segment

Features

- ▶ Dimmable
- ▶ Flicker Free
- ▶ LEDES rated for 50,000hrs
- ▶ Even and Uniform 360° Lighting
- ▶ Polymer Diffuser - Durable & Tough
- ▶ Operating Temp range - 40°F to 185°F
- ▶ Daylight color temperature 5000°Kelvin
- ▶ Light head Dimensions: 22" H x 17" D Weight: 30 lbs
- ▶ Area lit is approximately 10,956 yd² at 4.5 yds height
- ▶ Adjustable from Visible light to Infrared light (Optional)
- ▶ Adjustable Wattages 510W - 1020W - 1530W - 2040W - 2550W
- ▶ LED efficacy of 230 lm/w. 2550W LED efficacy is 586, 500 lumens
- ▶ Input Voltage Options: 12VDC, 24VDC, 48VDC AND 90VAC to 305VAC
- ▶ HEAVY Duty Impact Resistant road-case for transportation and storage
- ▶ Typical Amperage draw is 23 Amps @ 110V for 2550W; 4.6 Amps for 510W
- ▶ Total Luminous Flux of 335,836 lumens after diffuser and driver reductions
- ▶ State of the Art LEDs which have Extreme Stability and high Thermal ability
- ▶ Innovative LED Thermal Management System with PURE Aluminium heat sink
- ▶ Can be Retrofitted to conventional lighting towers, poles, plant and machinery



Features and Figures may be subject to change at any time without notice © Lunar-Lighting Innovations LLC 2025
Anti-Glare properties are dependent upon dimmer switch settings.

Lunar Lighting Innovations LLC

www.LunarLighting.com

Ph: +1 713 234 0270